

Technical Qualities

RAFFAELLO MADREPERLATO by OIKOS is a special Mother of Pearl finish for RAFFAELLO DÉCOR STUCCO. Based on lime putty, the product guarantees the substrate maximum vapour permeability and aids the natural diffusion of humidity through the wall, thus avoiding, over time, the formation of mould and bacteria. It has a low odour level, is non-flammable and is friendly to both humans and the environment.

Ideal Use

Decoration of walls, indoor furniture, any laminate surface, P.V.C., metal and wood.

Surface Preparation

Clean the surface to be decorated, removing any loose material and apply the recommended fixative, IL PRIMER by OIKOS in order to ensure perfect adhesion of the product to the surface.

Application Method

To achieve the perfect finish, apply the product in three coats using a steel trowel by OIKOS.

- **First and second coat:** Proceed to smooth over the entire surface with RAFFAELLO DÉCOR STUCCO, coloured as indicated on the colour chart in order to obtain a perfectly smooth, matt surface. Wait 6 ÷ 8 hours between each coat in order for them to dry.
- **Final coat:** Proceed to apply the colour of RAFFAELLO MADREPERLATO by OIKOS indicated on the colour chart, in patches well spaced between each other, thus obtaining an irregular pattern. After several minutes apply a very thin veil of product over the whole area at the same time smoothing and polishing the surface, obtaining a pearly, gloss effect depending on how much the surface is polished.

Finish

To enhance the gloss effect and protect it, apply after 6 ÷ 8 hours CERA STUCCO by OIKOS.

In order to obtain a higher level of water resistance and washability, apply after 4 ÷ 5 days PROTETTIVO PER STUCCO e MARMORINO by OIKOS.

Specifications

Thoroughly clean the surface, removing any loose material. Apply a fixative such as IL PRIMER by OIKOS and wait for it to dry. Apply two coats of a product such as RAFFAELLO DECOR STUCCO OIKOS and a third coat of a finish such as RAFFAELLO MADREPERLATO by OIKOS. For the working of the product a steel trowel must be used with the final effect imitating marble. All must be carried out in accordance with the norms of application, at a cost of m². inclusive of materials and labour.

The product

Composition	Lime putty, natural additives, pearlescent material, coloured earth and iron oxide based inorganic pigments.
Specific weight	1,2 kg/l ±3%
pH	12 ÷ 13
Viscosity	workable paste
Storage temperature	+2°C ÷ +36°C. (Keep from freezing)
Reaction to fire	Negative when the product is applied on a non inflammable surface; water based material with dry thickness of less than 0,600mm
Vapour permeability Sd	0,06 m (max allowed limit 2 m, DIN 52 615)
Emission limits of Volatile Organic Compounds (VOC) according to directive 2004/42/CE:	<ul style="list-style-type: none"> • Classification: A/I • VOC: 58g/l (max) • Limit Phase I (from 1.1.2007): 300g/l • Limit Phase II (from 1.1.2010): 200g/l
Colours	Shades of the colour chart
Packaging	Kg 1 – 5
Warning	<ul style="list-style-type: none"> • Avoid prolonged contact with the skin: if necessary, wash thoroughly with soap and water. If the irritation persists, consult a doctor. • Avoid contact with the eyes, in case of accidental contact, wash thoroughly with a sugar-water solution. If the irritation persists, consult a doctor.

The application

Dilution	Ready to use
Yield	10 m ² /kg
Application tools	Inox steel trowel by OIKOS
Fixative	IL PRIMER by Oikos
Base coat	RAFFAELLO DECOR STUCCO by Oikos
Protection	CERA PER STUCCO, PROTETTIVO PER STUCCO E MARMORINO by Oikos
Application temperature	+5°C ÷ +36°C (with relative humidity not exceeding 80%)
Drying time touch dry	1 hour (temperature = 20°C with relative humidity at 75%)
Drying time fully cured	20 ÷ 25 days (temperature = 20°C with relative humidity at 75%)
Tools cleaning	Water

Safety information

The product is free of heavy metals such as lead or chrome. It does not contain toxic solvents, aromatics or chlorides. There is no risk of any dangerous polymerisation.

The product is classified as hazardous pursuant to the provisions set forth in the Regulations (CE) 1272/2008 (CLP) and subsequent amendments and supplements.

For further information see the product Safety Data Sheet. Normal cautionary measures for the

handling of water based paints are advised. No special arrangements are required for the storage, movement and transportation of the product; the containers, residue, eventual spilt material should be cleaned up using absorbent inert material such as sand, soil etc. etc. and then disposed of in accordance with the regional and national regulations in force at that time. Transportation must be carried out in accordance with international agreements.